

Jack Weigh **AC|100** RFX™ Kit

Wireless or Cabled Top-of-Jack Weighing Systems for Military & All Commercial Aircraft



Accurate, Rugged & Universal Top of Jack Weighing Systems

Featuring RFX™ Wireless Weighing Technology for safe and convenient cable free top of jack weighing. Intercomp's **Jack Weigh Kits** use technologically advanced digital output load cells which perform an analog to digital conversion right at the cell itself for complete interchangeability of all components. This minimizes down time because it eliminates the need to recalibrate allowing spares to be swapped on site. The field proven load cell design mitigates influences of transverse forces, bending moments, torque and temperature variations for accurate and repeatable results.

The AC100 is a full function ruggedized CPU with IP67 enclosure capable of collecting and storing critical weight & balance data. Load cells and total weight are displayed on a large LCD readout with one touch controls for zero, arm length and center of gravity computation allowing for seamless integration to your existing weight and balance process. An on-board printer generates a report of all weight and C.G. related data, while up to 1,000 records can be stored in on-board memory and exported via RS232 or USB ports. The CPU communicates with load cells via wireless or cabled configurations.



JW-AC100

RFX™ Wireless Weighing Technology

- Up to 100,000lb (50,000kg) Capacity per Load Cell
- Accuracy of $\pm 0.1\%$
- Digital Output Load Cells
- Interchangeable Components
- Low-Profile Design to Fit Nearly Any Jack-to-Jack Point Envelope

Jack Weigh AC100 RFX™ Kit

- Configurations for Civil, Military & Commercial Aircraft
- Interchangeable Components Between Kits
- Includes AC100 CPU Digital Output Load Cells, Jack & Aircraft Adapters, Power Supply & Transport/Storage Case
- Models Approved to USAF PDLEEG17

Wireless & Cabled Kits Available



Load Cell & Accessory Case with Wheels & Telescoping Handle (AC100 Housed Separately)



AC100 CPU

- Display Individual Load Cell, Group & Total Weight, Mac% & C.G.
- Specific Hot Keys for Primary Functions
- Operates up to 32 Load Cells Simultaneously
- Operates on D-Size Batteries to 40 Hours Continuously
- On-Board Printer for Complete Report
- Store up to 1000 Aircraft Types & Arm Lengths
- Memory Storage & USB/RS232 Output

Load Cell Specifications

| | |
|------------|-------------------------------------------------------------------------------------------------------|
| Capacity | 5,000lb (2,500kg), 10,000lb (5,000kg), 25,000lb (12,500kg), 50,000lb (25,000kg), 100,000lb (50,000kg) |
| Graduation | User Selectable |
| Accuracy | ± 0.1% of Reading or 0.02% of Load Cell Capacity—Whichever is Greater |

AC100 CPU Specifications

CONTROLS

| | |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General | 40 CONTROL KEYS: On/Off, Reset, kg/lb, Zero, Clear, Enter, a Numeric Keypad, Adjust Screen, Back Light, Time/Date, Exit, Menu, Four Arrow Keys, Show Weight, Show Arms, Print, AC Info, Set Arm, Set Alt/Lat, Save Weigh Record, Recall Weigh Record, Clear Weigh Record, Save Arms, Recall Arms, Clear Saved Arms, & Output Saved Data |
| Display | 5.7" (145mm) Graphic LCD with Backlight |

ELECTRICAL

| | |
|--------------|-----------------------------------------------------------------------------|
| Voltage | 100 to 240 VAC, 50 to 60 Hz Universal Plug Kit Included |
| Batteries | 6 D-Cell Alkaline or NiMH Rechargeable Cells with External Access |
| Battery Life | 40 to 200 Hours Dependent on System Configuration, Printer, & Backlight Use |

RFX™ Wireless Radio Specifications

| | |
|----------------------|-------------------------------------------------------|
| Radio frequency | ISM 2.4GHz, 802.15.4 DSSS |
| License requirements | None. Pre-Approved US/FCC, CAN/IC, EUR/CE |
| Range | 200'/60m Indoor, 300'/90m Line of Sight |
| Batteries | 4 x AA NiMH Rechargeable or 4 x AA Alkaline Batteries |
| Battery life | 36 Hours with Alkaline Batteries |



Specifications subject to change without notice.



ISO 9001:2008 Registered

